

ARCONVERT SpA

Sede legale e amministrativa:

Strada del Linfano, 12
38062 Arco (TN), Italy
Tel. +39 0464.584444 r.a.
Fax Comm. +39 0464.532024
Fax Amm. +39 0464.584490
Fax Acq. +39 0464.531291

arconvert.com

Cap. Soc. €4.000.000 i.v.
Codice Fiscale e Registro
Imprese n. 01077840682
Partita IVA e VAT Code IT
n. 01192310223
N. Mecc. TN 007450
N. REA TN 122101

SPECIAL PRODUCTS DATA SHEET

CODE: **COATED 80 – ST5050S – KB85**

FACE MATERIAL		COATED 80	
ADHESIVE		ST5050S	
BACKING PAPER		KB85	
FACE MATERIAL : COATED 80			
<p>White, woodfree coated paper, gloss on one side. Machine coated paper for high quality labels. Ideal for multicolour prints requiring exceptional contrast and great detail.</p>			
Substance: 80 g/m ²	Caliper: 65 microns	Brightness: 95 %	Opacity: 86 %
		Glaze: 65 %	Tensile-strenght (MD-CD) 5.4—3.7 Kg/15mm
ADHESIVE: ST5050S			
<p>Modified acrylic adhesive in water emulsion. Adhesive suited to a wide range of applications, featuring high tack and adhesion values as well as good processing properties. Approved for indirect food contacts and corresponding to UNI-EN 71/3 "toys security" norms</p>			
Tack: 1200 g/25mm	Cohesion (min): 9 hours	Application temperature (min) + 5 °C	Service temperature (min) - 10 °C
			Service temperature (max) + 80 °C
BACKING PAPER : KB85			
<p>White paper coated and siliconized on one side. Backing paper for sheet fed printing system requiring an excellent dimensional stability.</p>			
Substance: 85 g/m ²	Caliper: 92 microns	Trasparency:	Opacity: 84%
			Tensile-strenght (MD-CD) 70-40 N/15mm
Date: 19.01.2012	Revision n°: 0	Report n°: FIXE-001	Q.C.Manager: Ing. Sabrina Leoni