DreamScapeTM Specification Sheet v:091115



Product Name:	DreamScape Terralon [™] , Terralon Smo	oth
Description:	PVC Free Eco-friendly digitally printable wallcovering , 54", 31% post consumer recycled content, for Latex, UV curable, Solvent + Eco Solvent inkjet printers	
Construction:	100% Terralon™ (Proprietary Polyester/Natural Fiber Technology)	
Weight:	14oz PLY / 435.2 G/PLM 9.3oz PSY / 315.3 G/PSM	
Availability:	Roll sizes: 54" x 25 yds, 54" x 50 yds, 54" x 100 yds - Trial Rolls (27"x15')	
Packaging:	3" core, wound print side out, wrapped in black back, Shipped in heavy duty reusable cardboard tube	
Application:	Standard commercial wallcovering pastes/primers and techniques	
Physicals:	Meets or exceeds federal specification CCCW-408D	
Environmental:	PVC & POA (Olefin) Free, No Plasticizers, No Phthalates, No Formaldehyde, No Chlorine, No Halogen, No Heavy Metals including: Cadmium, Mercury, Lead, or Zinc, and No Ozone Depleting Chemicals.	
	Minimum of 31% post-consumer recycled conten	nt
	Recyclable* Breathable** -very high permeability rating of 66 Perms based on ASTM E96 dry cup method Made with 100% water based adhesive systems No harmful off gassing Low Voc emitting	
Air Quality:	Meets California Section IAQ 1350- Third party certified by Berkeley Analytical Associates	
Flame and Smoke:	Class "A" Fire Rated – tested in accordance with ASTM-E84 Tunnel Test NFPA-101 (passed)	
LEEDS Eligibility:	Terralon [™] can contribute towards the earning of up to 7 LEED credits.	
	MR Credit 4.1 Recycled content 10% MR Credit 4.2 Recycled content 20%	NOTE: All LEED credits are based on the total construction of a building. Terralon [™] offers up to a 50% advantage over competitive products for achieving MR Credit 4.1 and MR Credit 4.2 because of its higher
	Conditionally-	percentage of post consumer recycled materials.
	MR Credit 2.1Contribution to project recycling programMR Credit 2.2Contribution to project recycling programMR Credit 5.1Manufactured local to the new constructionEQ Credit 4.1When mounted with use of low emitting adhesivesEQ Credit 4.6Contribution to low VOC emitting wall construction	
Warranty:	5 Year Warranty against manufacturing defects. Additional information regarding warranty is available on our website at http://www.dreamscapewalls.com/	
Comments:	**Permeable surface allows transfer of moisture to minimize possibility of mold and mildew growth. Terralon [™] is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation, and/or accumulation at wall cavities and wall surfaces, especially in warm, humid climates. Follow recommendations in the Terralon[™] Installation Instructions for best results.	
	and/or accumulation at wall cavities and wall sur	
	and/or accumulation at wall cavities and wall sur	results.