

AQUEOUS

BF600--

# BACKLIT FRONT MATTE WR 215

## Excellent Printing Compatibility For Latex

BACKLIT FRONT MATTE 215 is a backlit for use with dye and pigment inks. Coated substrates incorporates durability and a smooth matte, Ultra white finish print surface to provide consistent ink absorbing layer. The brilliant color expression are still stand out when the backlight was switched off. It is ideal for backlit signage applications, and provides high transmitted and ink density expressing vivid color and high resolution image. The printed side should always be faced to the observer as the inkjet coating and the print out are expected to be water-resistant.

### APPLICATION

light box advertising, illuminated displays, trade show and exhibition graphics, signage

#### Special Backlit application

- Cosmetics
- Fashion image
- Air Port & great image application

### SPECIFICATION

Caliper	215 micron (8.6 mil)
weight	270g
Base material	PET
Surface	Matte
Width	36", 50", 60"
Length	30m (100 ft)
Core	2"

### COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

#### Ink Compatibility

<b>Dye</b>		<b>Pigment</b>		<b>LATEX</b>	
------------	--	----------------	--	--------------	--

#### Printer Compatibility

HP				EPSON			CANON
LATEX	Dye	UV	Z-series	Dye	Ultra	K3	IPF
★	◎	★	★	◎	★	★	★

### TECHNICAL DATA

Caliper	215 micron	ASTM D645
Gloss	60° : 3.0 ≥ / 85° : 5.0 ≥	ASTM D2457
L.a.b	85 / 1.0 / -6.0	ANSI T (D50/2°/Abs/No)

### GUIDELINES

#### Printing Tip

Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%  
Use care in handling printed material, surface susceptible to abrasion  
To optimize the printing quality, printer need to be set for highest print quality.

#### Lamination:

Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended.

#### Storage:

It is recommended to store in the closed original packing in a cool and dry environment  
Temperature 10~25°C (50~77°F), Relative Humidity 50% RH

#### Shelf Life:

One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.  
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.