

NATURA MEDIA Inc.

12F ShinhanDM Bldg., Mapo Street 25, Mapo-gu, Seoul, Korea 121-708
Tel + 82-2-3788-0331, Fax + 82-2-3788-0326
Http://www.naturamedia.co.kr

FLAT DOT GLOSSY (ZSO550)

Details

- · Digital printing PVC media that has designed to remove bubbles with high performance
- · No need to use with special liquid mixture, excellent in work process
- · A semi-removal product that can be repositioned initially but the adhesive be stronger after positioned
- · This product can be installed by anyone without special techniques

APPLICATION

- · High quality printable
- · Promotion / Exhibition Hall Printings
- · Car Advertising In/Out-door Industrial Advertising

CHARACTERISTC

High Quality Printable
Adhesive Color: Transparent
Reworkable, Semi-removal

· Application Surface : Flat or curved sufaces

PHYSICAL	PROPERTY

Property	Metric Units	Test Method
Width	54"	
Length	30m (100ft)	
Core	3"	
Thickness(w/ adhesive)	130μm ± 10%	Micrometer
Tensile Strength	225kg/cm²	ASTM D638
Elongation	289%	ASTM D639
Adhesive	Initial 20 min. ≥700 g/in	
	middle 1days ≥900 g/in	180 peeling
	Final 3 days ≥1,100 g/in	
Service temp.	-45°C ~ 82°C	
Transfarency	± 0.5	Haze Meter
Gloss	70°≥	
Release liner's Thickness	0.14mm / 90g/m² ± 10%	

COMPATIBILITY

Ink Compatibility Eco-Sol, Solvent, Latex, UV

GUIDELINES

Printing Tip Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%

Use care in handling printed material, surface susceptible to abrasion

To optimize the printing quality, printer need to be set for hightest print quality.

Lamination: Lamination is optional. In order to protect the image from physical damage and to decrease image-fading,

overlaminate is recommended.

Storage: It is recommended to store in the closed original packing in a cool and dry environment

Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH

Shelf Life: One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affact results.



Head office (Korea)

Natura Media Inc.

Tel: +82-(0)2-3788-0365

Fax: +82-(0)2-3788-0326

sales@naturamedia.co.kr

Europe Branch (Belgium)
Natura Europe S.A
Tel: +32-65-225-509
Fax: +32-65-554-174
jh.hong@naturamedia.co.kr

USA Atlanta Branch Natura Media USA Inc. / SMP

Tel: +1-678-342-1720 Fax: +1-678-342-1788 pkwak@naturamedia.co.kr