

Technical Data Sheet

DIGITAL PRINTING PHOTO LUMINESCENT FILM

Stock Code	QTF301-124
LUMINESCENT VALUE:	The initial lighting source is 1000LX; activating time is 15 minutes, The luminescent value at 5 seconds ≥ 400 mcd/m ² , The luminescent value at 30 minutes ≥ 15 mcd/m ² , The luminescent value at 60 minutes ≥ 8 mcd/m ² , The luminescent value at 300 minutes ≥ 1.5 mcd/m ²
Service Life	Indoor 8 years Outdoor 5 years
Specification	1.24m x 45.7m per roll
Available colour	light green
Other Technical Data	<ol style="list-style-type: none"> 1. Surface film: PVC TYPE 2. Thickness of film: 0.16mm, Thickness of glue: 0.04mm Thickness of release paper: 0.18mm, total thickness of product 0.38mm with allowance of 5% more/less 3. Weight of release paper: 165g/m² with 5% more/less 4. Type of adhesive: Pressure sensitive type 5. Strength of adhesive: After sticking to the board for 24 hours, at the condition of 0.8kg, 5min, total length: 10 cm, falling length ≤ 2cm 6. Operation temperature: 10°C - 30°C 7. Working Temperature: -20°C - 60°C After sticking to the board for at least 7 days 8. Storage temperature: 0°C - 30°C

Note:

All above information shall only be used as a guide; buyer shall independently test and determine product suitability. All technical data is subject to change without prior notice.

Johannesburg:

36 Loper Avenue, Areoport, Spartan, Kempton Park, South Africa
Tel: +27(0)11 974 0080

Durban:

Unit 6 & 6, 3 Hillhead Road Mount Edgecombe, Durban, South Africa
Tel: +27(0)31 539 7663