

Technical Data Sheet

PET REFLECTIVE SHEETING

Stock Code	QTM3100										
Product description:	PET type, Unprintable & Untearable Reflective Sheeting Excellent for computer cutting 1. Available color: yellow, red, green, blue 2. Type of Adhesive: Pressure-Sensitive Type 3. Strength of Adhesive: at the condition of 0.8kg, 5min, total length: 10cm, the falling Length ≤ 2cm 4. Working temperature: -20 °C --- 60 °C 5. Color chromaticity: Standard light source: D65 Observation condition: 45/0 Observation angle: 2 °C.										
Colour	Colour chromaticity								Luminance factor		
	X	Y	X	Y	X	Y	X	Y			
Yellow	0.545	0.454	0.464	0.534	0.427	0.483	0.487	0.423	0.16 - 0.40		
Red	0.690	0.310	0.658	0.342	0.569	0.341	0.595	0.315	0.03 -0.10		
Green	0.007	0.703	0.206	0.399	0.177	0.362	0.248	0.409	0.03.10		
Blue	0.078	0.170	0.137	0.038	0.210	0.160	0.150	0.220	0.01-0.10		
	6. Coefficient of retro reflection										
Observation angle	Entrance										
	Angle		White		Yellow		Red		Green	Blue	
0.33		-4		30		15		5		4	2,5

Note:

All above information shall only be used as a guide; buyer shall independently test and determine product suitability. All technical data is subject to change without prior notice.

Johannesburg:

36 Loper Avenue, Areoport, Spartan, Kempton Park, South Africa
Tel: +27(0)11 974 0080

Durban:

Unit 6 & 6, 3 Hillhead Road Mount Edgecombe, Durban, South Africa
Tel: +27(0)31 539 7663