

Technical Data Sheet

COMMERCIAL GRADE (PVC) REFLECTIVE FILM

Stock Code	QTM3800								
Product description:	<p>Feature: untearable, easy operation, can be digital printed.</p> <p>Application: advertisement signs, temporary work zone signs.</p> <p>Service life: 3 years</p> <p>Specification: 1.24m x 15,7m</p> <p>Available color: white, yellow, red, green, blue, orange, lemon yellow, fl.yellow</p>								
Other technical Data	<ol style="list-style-type: none"> Surface Film: PVC Type Thickness of film: 0.24mm, thickness of glue: 0.03mm Thickness of release paper 0.18mm, total thickness of products: 0.38mm Weight of release: Paper 145 g/sqm Type of adhesive: Pressure -sensitive type Strength of adhesive: at the condition of 0.8kg, 5min, total length: 10 cm, the flling length ≤ 2cm Operation temperature: 5C - 30C Working temperature: 20C - 60C Weight per sqm: 445g Colour chromaticity: Standard light source: D65 Observation condition: 45/0 Observation angle: 2 Degree 								
Colour	Colour chromaticity						Luminance factor		
	X	Y	X	Y	X	Y			
White	0.350	0.360	0.300	0.310	0.285	0.325	0.355	0.375	≥ 0.27
6. Coefficient of retro reflection (Min Value)									
Observation angle	Entrance								
	Angle	White							
0.2	-4	35							

Note:

All above information shall only be used as a guide; buyer shall independently test and determine product suitability. All technical data is subject to change without prior notice.