



Cnr Riley Street & Jan van Riebeeck Drive, Beaconvale 7500, Parow, South Africa **Tel:** +27(0)21 932-3602 **Email:** <u>r.spolander@seldenrod.co.za</u>

Technical Data Sheet

Medium Tack - Application Tape

STOCK CODE	T2402-122
PRODUCT INFORMATION	Application Tape based on a special high tensile impregnated paper coated with a natural rubber (Medium Tack). The tape is suitable for transferring lettering and symbols cut from all qualities of self adhesive vinyls. Especially to be emphasised are the following properties: • Ageing- and UV-stabilised natural rubber. • The Application Tape is easy to unroll and position and will not stretch or curl. • Constant adhesion within a small tolerance. • Suitable for wet application.
TECHNICAL DATA	Carrier: Special paper, impregnated Adhesive: Natural rubber Adhesion [N/cm]: 2,10 +/- 10 % Thickness [mm]: 0,10 +/- 5 %
STANDARD	610mm X 91.4m
DIMENSIONS	1220mm x 91.4m
SAFETY DATA SHEET	When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities

Note:

All above information shall only be used as a guide; buyer shall independently test and determine product suitability. All technical data is subject to change without prior notice.