

Cnr Riley Street & Jan van Riebeeck Drive, Beaconvale 7500, Parow, South Africa Tel: +27(0)21 932-3602

Email: r.spolander@seldenrod.co.za

## **Technical Data Sheet**

## **High Tack - Application Tape**

STOCK CODE	T2400
PRODUCT INFORMATION	Transparent application tape based on a single sided embossed polypropylene film, with excellent flatness. It is dimensionally stable, easy to unroll position and will not stretch or curl. Suitable for transferring self- adhesive signs, logos and lettering produced from cast or calendared CAD/CAM plotter films with matt and brilliant surface; especially to be emphasized are the following properties:  As the tape does not curl, wrinkling is avoided during lamination of large lettering. The film adjusts perfectly to the surface.  The plasticizer resistant adhesive guarantees a strong initial tack to all types of vinyl films. The application tape is easily removed without leaving any residue, even after being left for a period of time.  Suitable for wet application.  The film can be torn transversally, which facilitates handling.  The embossed surface allows the film to be easily unrolled without any electrostatic charging.
TECHNICAL DATA	Carrier: Polypropylene film, orange peel surface Adhesive: Acrylic Adhesion [n/cm]: 1, 10 +/-10% Thickness [mm]: 0, 11 +/-5%
STANDARD DIMENSIONS	1.220mm x 100m 1.000mm x 100m
SAFETY DATA SHEET	When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non- hazardous product in accordance with the current GEFSTOFFV and EU criteria. Therefore it is not necessary to prepare a material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with reach Regulation (EC) no. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the national/ local authorities.

\*The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.

Note:

All above information shall only be used as a guide; buyer shall independently test and determine product suitability. All technical data is subject to change without prior notice.