


## Technical Data Sheet

### Ferro Film with White PET

<b>Stock Code</b>	
<b>Construction</b>	 <p>White PET 0,1mm        Magnetic Receptive Layer 0,08mm</p>

### Material Properties

<b>Total Thickness</b>	0,18mm (+/- 0,02mm)
<b>Standard Width</b>	1270mm, 1370mm (+3mm/-0)
<b>Standard Length</b>	50m(+0,5m/-0)
<b>Magnetic Receptiveness:</b>	>3,5g/cm <sup>2</sup> The magnetic receptiveness is tested on Quality standard semi - anisotropic flexible magnetic sheet of 0,75mm thickness (magnetic pull 42g/cm <sup>2</sup> )

### Printability:

Large format digital printer: Eco - Solvent inks	YES
Large format digital printer: Eco - UV Inks	YES

*\* Users should do preliminary tests to confirm printability before production. Printing problems may occur on certain machines due to ink problems or other technical problems other our knowledge*

<b>Note:</b>	<i>All above information shall only be used as a guide; buyer shall independently test and determine product suitability. The mentioned data are average of test results and should not be used for the purpose of lawsuit and</i>
--------------	--

**Johannesburg:**  
 36 Loper Avenue, Areoport, Spartan, Kempton Park, South Africa  
**Tel:** +27(0)11 974 0080

**Durban:**  
 Unit 6 & 6, 3 Hillhead Road Mount Edgecombe, Durban, South Africa